

Automated Container Terminals: Past, present, and future

AAPA Marine Terminal Management Training Seminar
September 17-21, 2012
Baltimore, Maryland

Andrew Cairns, PE PMP
Regional Port Business Line Leader
AECOM

Presentation Overview

- Examples of Implementation Worldwide
- What's Settled and What's Uncertain Regarding Automation Concepts
- Challenges for Automation Planning
- Architectural Issues Related to Automation
- Civil Engineering Design Issues for Automation
- Future Concepts

Automation on Marine Container Terminals

- Data capture
 - Gate, Crane, Rail, CY OCR
 - RFID
- *Container lifting equipment without drivers on the machine*
 - *RMGs, Strads*
 - *Largely automated*
 - *Remote drivers as needed (gate and exception)*
- *Horizontal transport*
 - *Automated guided vehicles (lift or standard)*
 - *Automated strads/shuttles*
- Vessel mooring (Vacuum based mooring vs ropes)

Strengths of Automated Terminals

- **Safety**
 - Strict separation of trucks and cranes
 - Fewer personnel
- **Storage density**
 - All containers grounded (not wheeled)
 - Automated cranes allow for easy re-handling
- **Low Emissions**
 - Electrically powered yard cranes
 - Short travel distance for horizontal transport
- **Low operating cost**
 - More efficient use of labor
 - Lower maintenance costs
 - Lower energy costs
- **Fewer Damaged Containers**
 - More accurate handling
- **Less Noise**
 - Boxes not hitting each other

Tour of Automated Terminals Worldwide

Thamesport, UK



ECT, Rotterdam



ECT, Rotterdam



Altenverder, Hamburg



Altenverder, Hamburg

2nd quay crane hoist is automated



Nested ASCs that can Pass are Unique to Altenverder




With end loaded CY systems, trucks back up to the
landside end of the CY stacks and are served by remote operators
With no need to creep forward, trucks can shut off engines
while waiting for service



Console for Remote Yard Crane Operations for Gate Service in Hamburg

A camera on each corner of the spreader shows an image here



This joystick controls the electric crane

Automated Strad Terminal in Brisbane, Australia



Note the fence to separate automated and manual areas

Controlled labor access to reefer area

“Airlock” Access to Reefer Area in Brisbane



Gate Service in Brisbane is Done Via Remote Control in the Lanes



APMT Norfolk



APMT Norfolk



Imagery Date: Apr 7, 2010

36°52'28.51" N 76°21'19.41" W elev 2 m

©2010 Google

AECOM

Eye alt 1.62 km

APMT Norfolk Wharf



AMPT Norfolk Landside Operation



DPW Antwerp – Conversion of Strads to Strad+ASC



DPW Antwerp ASC Interfaces

Gate/ rail Interface (trucks)



Vessel Interface (strads)



Euromax Rotterdam



Euromax Rotterdam



CTB Hamburg



TTI Algeciras – Opened May 2010



VERTICAL LAYOUT DESIGN

Highlights of the World's ASC Terminals

Location/ start date	Cranes per block	Stack width (boxes)	Waterside transport	Landside transport
Thamesport/1990	2 on same rails	9/7	Trucks drive to side of ASC	Trucks back-in to landside of ASC row
ECT Rotterdam/ 1993	1	6	AGVs to end of ASC	Trucks served via strad interface
CTA Hamburg/ 2002	2 on separate rails	10	AGVs to end of ASC	Trucks back-in to landside of ASC row
APMT Norfolk/ 2007	2 on same rails	8	Manned shuttles at end of ASC	Trucks back-in to landside of ASC row
DPW Antwerp/2007	2 on same rails	10	Manned shuttles at end of ASC	Trucks back-in to landside of ASC row
Euromax Rotterdam/2008	2 on same rails	10	AGVs to end of ASC	Trucks back-in to landside of ASC row
CTB Hamburg/2009	3, on two sets of rails	10	Manned shuttles at end of ASC	Trucks back-in to landside of ASC row
TTI Algeciras/ 2010	2 on same rails	8	Manned shuttles at end of ASC	Trucks back-in to landside of ASC row

What seems to be settled in 2012?

- Street trucks back into the ends of the yard stacks
- All containers under automated cranes, no manual areas for reefers, empties, etc. (all but oversize)
- Work to crane backreach makes automated transport easier
- ASC width from 8-10 containers seems ideal
 - Wider cranes are heavier and more expensive and may not keep up with peak stevedoring requirements
 - Narrower cranes are not space efficient and result in more cranes than needed
- ASC height of 1-over-5 : Taller stacks are hard to manage and may require wider spacing to allow for rope reeving
- No one outside of Hamburg has used pairs of ASCs on different rail gages
- No one outside of Hamburg has used more than two ASCs per row

What is still being debated in 2012?

- Manual vs automated horizontal transport
- Coupled (AGV), semi coupled (lift-AGV, cassette AGV), or decoupled (shuttles) transport
- Maximum and minimum practical ASC row length
- Feasibility of using 3 ASCs per row for long rows
- Options to increase yard density vs traditional ASCs
- Benefits of multi-pick ASCs and transports
- Parallel vs perpendicular layouts, especially for narrow terminals (TraPac, Pier S) or transshipment terminals.
- Best strategy for rail service, especially on terminals with 33%+ vessel moves via rail.
- Best way to phase from RTG+tractors to automation

Why is Automation so Appealing?

2011 San Pedro ILWU Cost Structure

- Dock crane excluding tractors and yard support ~ \$1600/hr
- Seven tractors per crane ~ \$800/hr
- Top pick crew ~ \$225/hr
- RTG crew ~ \$650/hr
- Automation savings:
 - Dock cranes are (probably) more productive
 - Fewer manual transport required with ASCs (shorter distance)
 - Zero transport required with AGVs or Autos Shuttle
 - Per-crane yard crane costs of ~ \$50/hr (1 driver per 4 ASCs at \$200/hr)

Automation Planning on Non-rectangular Terminals

- What's the shortest and longest practical ASC length?
- Is it feasible to use one, or three, ASCs per row?
- When do you align rows parallel to berth, or parallel to other long terminal border?
- What's the best way to access the railyard?
- Case studies
 - TraPac
 - Pier S
 - WBCT

Planning and Design Challenges




TraPac Base Case Layout




ASCs either parallel or perpendicular to wharf
2 ASCs per row

TraPac Option 2 – a more radical approach




ASCs parallel to the IY
Some rows with 3 ASCs

Pier S Option 1 combines parallel and perpendicular ASCs





AGVs to IY?
3 ASCs over 2 Rows?

Pier S Option 2 uses side loaded RMGs in the Shallow but Broad Terminal CY



Pier S Option 3 Nests the RMGs for more Storage





One Option at WBCT

- ASCs with manual tractors
- Similar to Thamesport/NYCT concept
- Can be easily converted to end loaded optoins



Simulation and Emulation to Support Planning



Terminal fleets will see a transition from hustlers and bombcarts to shuttle carriers or AGVs



Automation and Architectural Issues

- Buildings should be flexible enough to service near term and long term equipment fleets
- Existing maintenance buildings may need to be modified
- New maintenance buildings may be configured to accept final equipment while accommodating interim equipment



Civil Design Challenges with Automated Terminals

- Pavement
 - Asphalt vs. gravel
 - Rutting
 - Drainage
- Rails on Gravel vs Beams
- Settlement
- Electrical utilities




Electricity Related Planning Issues

- Optimum sizing of infrastructure
 - Oversized substations cost more to build
 - Oversized substations draw more power at idle
- Larger numbers of cranes will lower the mean draw per crane due to asynchronous activity (some are generating power while some are drawing power)
- Can TOS be tuned to run cranes with lower power during off-peak activity (esp gate moves)?
- Can TOS be tuned to time overhead moves when power is cheapest (usually at night)?
- Do operators and Ports care about high-detail power and emissions data reports?


Future Concepts to Contemplate

- Direct yard crane / dock crane handoffs
- Rail based transport (ZPMC etc.)
- Nested cantilever RMGs
- New Container Handling Technologies

ASC Terminals Require a Large Maneuvering Area Waterside of the ASC Blocks




CTA Hamburg = 345'




APMT Virginia = 330'

A Space Efficient Terminal!



Could an RMG pick/set directly to dock crane
Backreach?

Cantilever RMGs vs ASCs



- More slots per acre
- More flexible crane assignment
- More buffer slots
- Less RMG rail required
- More expensive cranes
- Limited terminal depth with two rows
- Complex TOS required


ZPMC Automation Module



Paceco SegCart Concept



http://www.youtube.com/watch?feature=player_detailpage&v=ty-PuF6VICM



Conclusions

- Fundamentals of terminal automation have been well proven
 - Driverless RMGs can handle containers easily
 - Automated transport vehicles can achieve fair, if not great, productivity
 - Off the shelf software and sensors can coordinate terminal activity
- Terminal automation is relatively new, with many challenges and areas of improvement still to come
 - Decoupled ASC operations
 - Automated rail transfer
 - Non-rectangular terminals
 - Conversion from existing operations
- Careful planning, analysis, and expert integration assistance is important for project success

Speaker Contact Information

- Andrew Cairns, PE PMP
AECOM
20 Exchange Place
New York, NY 10005
Phone: 510-844-0549
Email: andrew.cairns@aecom
Web: www.aecom.com